








Features

- EPISTAR chips
- Energy saving and eco-friendly
- No UV light
- Long life span
- Maintenance free, use and installation easily
- Widely used - including backlighting in alcoves, stalcoves, stairs, ceilings, shop windows, furniture,
- Good quality
- Certificates CE, ROHS
- Two years warranty
- Packing: 5 meters per reel in an anti-static bag, 20 bags per carton

LED Strips												
Photo	Product code	EAN	Color	Color Temperature	LED type	LED QTY [pcs/m]	Power/ 1 m	Life time	Angle	Voltage	Size [W x H]	International Protection
	PL-FS352812WW60-IN	5906160707863	Warm white	2700-3200K	SMD 3528	60	4,8W	30.000h	120°	12V DC	8mm x 2.2mm	IP20
	PL-FS352812W60-IN	5906160707870	Cool white	6500-7000K	SMD 3528	60	4,8W	30.000h	120°	12V DC	8mm x 2.2mm	IP20
	PL-FS352812R60-IN	5906160707887	Red	/	SMD 3528	60	4,8W	30.000h	120°	12V DC	8mm x 2.2mm	IP20
	PL-FS352812G60-IN	5906160707894	Green	/	SMD 3528	60	4,8W	30.000h	120°	12V DC	8mm x 2.2mm	IP20
	PL-FS352812B60-IN	5906160707900	Blue	/	SMD 3528	60	4,8W	30.000h	120°	12V DC	8mm x 2.2mm	IP20
	PL-FS352812Y60-IN	5906160707917	Yellow	/	SMD 3528	60	4,8W	30.000h	120°	12V DC	8mm x 2.2mm	IP20
	PL-ML352812WW60-IP54	5906160708617	Warm white	2700-3200K	SMD 3528	60	4,8W	50.000h	120°	12V DC	8mm x 3mm	IP54
	PL-ML352812W60-IP54	5906160708624	Cool white	6500-7000K	SMD 3528	60	4,8W	50.000h	120°	12V DC	8mm x 3mm	IP54
	PL-FS352812R60-OUT	5906160707948	Red	/	SMD 3528	60	4,8W	30.000h	120°	12V DC	8mm x 2.8mm	IP65
	PL-FS352812G60-OUT	5906160707955	Green	/	SMD 3528	60	4,8W	30.000h	120°	12V DC	8mm x 2.8mm	IP65
	PL-FS352812B60-OUT	5906160707962	Blue	/	SMD 3528	60	4,8W	30.000h	120°	12V DC	8mm x 2.8mm	IP65
	PL-FS352812Y60-OUT	5906160707979	Yellow	/	SMD 3528	60	4,8W	30.000h	120°	12V DC	8mm x 2.8mm	IP65
	PL-ML352812WW120-IP54	5906160708587	Warm white	2700-3200K	SMD 3528	120	9,6W	50.000h	120°	12V DC	8mm x 3mm	IP54
	PL-ML352812W120-IP54	5906160708594	Cool white	6500-7000K	SMD 3528	120	9,6W	50.000h	120°	12V DC	8mm x 3mm	IP54
	PL-FS505024WW48-IN	5906160708426	Warm white	2700-3200K	SMD 5050	48	12W	30.000h	120°	24V DC	10mm x 2.0mm	IP20
	PL-FS505024W48-IN	5906160708433	Cool white	6500-7000K	SMD 5050	48	12W	30.000h	120°	24V DC	10mm x 2.0mm	IP20
	PL-FS505024R48-IN	5906160708440	Red	/	SMD 5050	48	12W	30.000h	120°	24V DC	10mm x 2.0mm	IP20
	PL-FS505024G48-IN	5906160708457	Green	/	SMD 5050	48	12W	30.000h	120°	24V DC	10mm x 2.0mm	IP20
	PL-FS505024B48-IN	5906160708464	Blue	/	SMD 5050	48	12W	30.000h	120°	24V DC	10mm x 2.0mm	IP20
	PL-FS505024Y48-IN	5906160708471	Yellow	/	SMD 5050	48	12W	30.000h	120°	24V DC	10mm x 2.0mm	IP20
	PL-FS505024WW48-OUT	5906160708488	Warm white	2700-3200K	SMD 5050	48	12W	30.000h	120°	24V DC	10mm x 2.6mm	IP65
	PL-FS505024W48-OUT	5906160708495	Cool white	6500-7000K	SMD 5050	48	12W	30.000h	120°	24V DC	10mm x 2.6mm	IP65
	PL-FS505024R48-OUT	5906160708501	Red	/	SMD 5050	48	12W	30.000h	120°	24V DC	10mm x 2.6mm	IP65
	PL-FS505024G48-OUT	5906160708518	Green	/	SMD 5050	48	12W	30.000h	120°	24V DC	10mm x 2.6mm	IP65
	PL-FS505024B48-OUT	5906160708525	Blue	/	SMD 5050	48	12W	30.000h	120°	24V DC	10mm x 2.6mm	IP65
	PL-FS505024Y48-OUT	5906160708532	Yellow	/	SMD 5050	48	12W	30.000h	120°	24V DC	10mm x 2.6mm	IP65
	PL-FS505012WW60-IN	5906160708129	Warm white	2700-3200K	SMD 5050	60	14,4W	30.000h	120°	12V DC	10mm x 2.0mm	IP20
	PL-FS505012W60-IN	5906160708136	Cool white	6500-7000K	SMD 5050	60	14,4W	30.000h	120°	12V DC	10mm x 2.0mm	IP20
	PL-FS505012R60-IN	5906160708143	Red	/	SMD 5050	60	14,4W	30.000h	120°	12V DC	10mm x 2.0mm	IP20
	PL-FS505012G60-IN	5906160708150	Green	/	SMD 5050	60	14,4W	30.000h	120°	12V DC	10mm x 2.0mm	IP20
	PL-FS505012B60-IN	5906160708167	Blue	/	SMD 5050	60	14,4W	30.000h	120°	12V DC	10mm x 2.0mm	IP20
	PL-FS505012Y60-IN	5906160708174	Yellow	/	SMD 5050	60	14,4W	30.000h	120°	12V DC	10mm x 2.0mm	IP20
	PL-ML505012WW60-IP54	5906160708600	Warm white	2700-3200K	SMD 5050	60	14,4W	50.000h	120°	12V DC	12 mm x 3mm	IP54
	PL-ML505012W60-IP54	5906160708631	Cool white	6500-7000K	SMD 5050	60	14,4W	50.000h	120°	12V DC	12 mm x 3mm	IP54
	PL-FS505012R60-OUT	5906160708204	Red	/	SMD 5050	60	14,4W	30.000h	120°	12V DC	10mm x 2.6mm	IP65
	PL-FS505012G60-OUT	5906160708211	Green	/	SMD 5050	60	14,4W	30.000h	120°	12V DC	10mm x 2.6mm	IP65
	PL-FS505012B60-OUT	5906160708228	Blue	/	SMD 5050	60	14,4W	30.000h	120°	12V DC	10mm x 2.6mm	IP65
	PL-FS505012Y60-OUT	5906160708235	Yellow	/	SMD 5050	60	14,4W	30.000h	120°	12V DC	10mm x 2.6mm	IP65

Features

- EPISTAR chips
- Energy saving and eco-friendly
- No UV light
- Long life span
- Maintenance free, use and installation easily
- Widely used - including backlighting in
- Widely used - including backlighting in alcoves, stairs, ceilings, shop windows, furniture, shelves, buildings, backlight or edge light for signage letters
- Good quality
- Certificates CE, ROHS
- Two years warranty
- Packing: 100 meters per reel (rope light 3528) and 50m per reel (rope light 5050)

Rope Lights												
Photo	Product code	EAN	Color	Color Temperature	LED type	LED QTY [pcs/m]	Power/ 1 m	Life time	Angle	Voltage	Size [W x H]	International Protection
	PL-SR3528-60-WW-OUT	5906160708549	Warm white	2700K-3500K	AC LED SMD rope light 3528	60	4W	30.000h	120°	AC 220-240V	8mm x 6mm	IP68
	PL-SR3528-60-W-OUT	5906160708556	Cool white	5500K-6500K	AC LED SMD rope light 3528	60	4W	30.000h	120°	AC 220-240V	8mm x 6mm	IP68
	PL-SR5050-60-WW-OUT	5906160708563	Warm white	2700K-3500K	AC LED SMD rope light 5050	60	12W	30.000h	120°	AC 220-240V	12mm x 6mm	IP68
	PL-SR5050-60-W-OUT	5906160708570	Cool white	5500K-6500K	AC LED SMD rope light 5050	60	12W	30.000h	120°	AC 220-240V	12mm x 6mm	IP68